

2023 FWD HOBO (Gut & Go)

Domination Motorsports Southern #9 Memorial Tour

Austin Johnson- (217) 248-0886

General Rules & Expectations:

1. ALL RULES MUST BE FOLLOWED OR YOU WILL NOT RUN
2. **Drivers & Riders must wear seat belt, helmet, fire suit jacket, and long pants while participating.**
3. ALL Drivers & Riders must attend the drivers meeting.
4. During event you are given 1 minute to make an aggressive hit or will be disqualified.
5. You **MUST** run a roof sign.
6. Drivers & Riders are not allowed to drink alcohol before they participate. If found with alcohol in system you will not run, no exceptions. **ZERO TOLERANCE RULE!!!**
7. **Austin Johnson- 217-248-0886** call before you assume something will pass. If it is not in the rules and doesn't tell you, you can do it, then don't! We can't stress that enough!! **CALL FIRST!!!**

THIS IS NOT A SET OF RULES BUT A SET OF GUIDELINES OF HOW TO BUILD YOUR CAR. IF IT DOESN'T SAY YOU CAN SPECIFICALLY DO SOMETHING THEN YOU CAN'T!

Show Rules:

1. You have 1 minute to make an aggressive hit. After 1 minute that car is disqualified. That is 1minute total. An aggressive hit is solely at the discretion of the officials.
2. For safety, **DO NOT HIT THE DRIVERS DOOR!!**
3. You are given 2 fires- 1st one we put out and the 2nd one you are done for that round.
4. Rollovers- you may keep going as long as car is deemed safe.
5. Watch the officials. If they are trying to get your attention, there is a reason.
6. No holding or pinning, you must back up and show day light. You may not pin to win!

**THIS IS A SET OF GUIDELINES OF HOW TO BUILD YOUR CAR.
IF IT DOESN'T SAY YOU CAN SPECIFICALLY DO SOMETHING THEN YOU CAN'T!!!**

Car Preparation:

NO PAINTING OR UNDERCOATING OF THE FRAME. NO BUFFING OR GRINDING FRAMES OR BODIES EXCEPT WHERE WELDING IS SPECIFICALLY ALLOWED IN THESE RULES. NO PAINTING IN THE INSIDE OF THE BODY OR CAR. IF THIS IS DONE THE CAR WILL NOT BE INSPECTED.

1. May be any 1980's and newer front-wheel drive car (Wheelbase up to 112") with a V4 or V6 engine and **must be the original engine** for that car. No modifications or carb conversions of any kind besides a simplified wiring harness.
2. Remove all glass, mirrors, plastic, outside body chrome & turn signals. Vehicles must be swept clean of all debris. Also, must remove ALL carpet, dash, headliner, rear seats, and any other flammable materials.
3. ZERO crease enhancement, ZERO sheet metal or frame shaping, forming or folding.
4. Hoods must be 100% in stock location and open for inspection. Must have a minimum 12" opening on hood in case of a fire.
5. Hoods may be fastened in 4 places. 2 places with the core support all thread and 2 places with 2 strands of #9 wire. Trunks may be fastened in 4 places with 2 strands of #9 wire only, no all thread. Trunk may have a single 90 degree bend. You may weld doors 6 inches total on each vertical seam only 2"x1/8" Strap. Drivers door may be welded 12 inches total on vertical seams only 2" x 1/8" strap. Do not weld hood or trunk!
6. Body mounts and spacers to remain stock and in place. If they are broken or rusted out, a single piece #9 wire may be substituted. No body bolt changing allowed. **DO NOT EVEN TOUCH THEM!!!**
Exception: You may replace two front body mounts with two 5/8" threaded rod with eight 3inch washers and 4 nuts, Bottom nut and washer must be inside frame and may extend through hood. ZERO welding allowed to mount this rod.
7. #9 wire or chain required in front windshield.
8. Battery must be relocated to the interior of the vehicle and properly secured and covered. If you have a passenger please make sure its in a safe place, secured & covered.
9. Must disable airbags.
10. Gas tanks **MUST** be moved behind the seat in the center. All fuel lines running inside the car must be covered. Original gas tanks are not allowed, must be an aftermarket metal or aluminum fuel cell. Gas tanks must be mounted 8-inches off the floor and all sheet metal.
11. 4-point square cage only 60" max in length with one 2x3 down tube to sheet metal only per side. Max 60-inch side bars 6-inch max. Halo bar is **MANDATORY** and must be attached to the backseat bar and floor sheet metal.

- **Gas Tank Protector: (Highly Recommended)**

Dimensions: 24 inches wide, 24 inches long, 6 inches tall & 8 inches from everything including the rear and floor sheet metal.

12. **Mandatory:** Driver's doors must be padded and have a bar or plate on driver's door that is at least 3/16-inch-thick but no more than ONE inch thick- on the inside, outside or both for safety. Plate or Bar must cover the door, not less than 6 inches and not more than 10 inches past each front and rear seams. (NO grader blades, channel iron or I-beams allowed). IF you have a passenger please follow the same rules for the passengers door.

13. Must use factory pedals, brakes and steering wheel.

- You are allowed an aftermarket shifter; it may not be mounted in any way that strengthens the car.

Everything else must be factory for the year, make and model of the car you are running.

14. You may weld any stock factory car bumper and you may weld the stock bumper bracket for the car or the bumper to the frame 4 inches from the back of the bumper, single pass only. In addition, you may weld (4) one-inch welds on the back side of the bumper. All bumper material longer than 4" back must be removed.

- Shocks may be collapsed and welded. All shocks and brackets in stock location only and extended one inch in front of frame. Again, all bumper brackets and shocks must be in stock location.
- **Or** you may shorten to one inch in front of the core support space and hard nose with no shocks or brackets on car.
- **Or** you may chain, one piece of chain per side BOLTED from the mount to mount to hold on the bumper.

Instead of a loaded factory bumper you may use a piece of 4"x4"x1/4" flat tubing in its place with original bumper shocks for the car you are running. NO POINT.

15. Any tires are fine, including solid rear forklift tires. You may weld in full centers but no other bracing or supports allowed on the wheels.

ONLY welding allowed is doors, bumpers & cage.

This build should only take 3 days, if you spend more than that you are overbuilt for this class.

If you call me on these, the answer is most likely NO!

Simple rules, simple build- keep it that way!

DO NOT get "creative" or read into these rules, lets get back to the basics.

Again, if it is not clearly described above, it is not allowed.

IF THE RULES DO NOT SAY YOU CAN DO IT, YOU CAN'T!!!!!!

Repair Plate Rules:

Fresh Cars: (2) 6x6x1/8"

Plates must be 1-inch apart including the weld; 1/2" weld max.

They cannot touch or be attached to the driveline components at all

Pre Ran: (4) 6x6x1/8"

Plates must be 1-inch apart including the weld; 1/2" weld max.
They cannot touch or be attached to the driveline components at all.

Domination Motorsports